MMP Industries Limited

B-24, MIDC Area, Hingna Road, Nagpur-440016. CIN: L32300MH1973PLC030813 Tel: (07104) 668000, Email: sales@mmpil.com Web: www.mmpil.com



TECHNICAL DATA SHEET

Product Name : Aluminium Powder for Explosives

Grade : SDS

Product Description :

Aluminium powders are used as a sensitizer in the manufacture of explosives. Different grades are processed to meet the specific needs of explosives manufacturers. Flake Aluminium powders add strength to the slurry explosives, particularly its sensitization property. Aluminium powder is generally hazardous in nature, but these powders are properly coated with fatty acids and special properties are generated to enhance its safety in handling and even in aqueous medium of different pH.

Characteristics	Test Method	Specification
Free Al. Purity % (min.)	IS-438	88
Wet Sieve Analysis Retention on 45μm % (max.)	ISO 1247	12
Water Coverage Area cm²/gm	IS-438	9000 TO 12000
Fatty Acid % (max.)	IS-438	4
Wettability (minutes) min	In House	10
Bulk Density gm/cc	In House	0.20 ± 0.02
Particle Size Distribution D50 (μm)	Sympatec (Helos BF/BR - Magic)	13 - 18

^{*}Aluminium product is made out of aluminium ingots of 99.7% min purity.

Wet sieving with mineral spirit as rinsing liquid.

Standard packing: 20 & 25 kg net content in HDPE bags with antistatic liner.

The data on this technical data sheet correspond with the current status of our knowledge & experience. The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights. We reserve the rights to alter any product data as a result of technical progress or further developments in the manufacturing process.